


ANTISEIZES

| PRODUCTS | BENEFITS | APPLICATIONS | BASE | BASE OIL | NLGI GRADE | OPERATING TEMP. RANGE °C |
|--|---|--|-----------------------|----------|------------|--------------------------|
| AS 10/60/80 Concentrated MoS₂ Antiseize Pastes | <p>High content of MoS₂ provides excellent antiseize and load carrying capacity. Avoids seizures, stick-slips. Good resistance to most chemicals, water, grease & oil.</p> | <p>As an antiseize for threaded assemblies like valves, spindles, bolts, studs, nuts, lead screws and others. For priming of guide ways, machine slide ways, high load slow moving plain bearings. For press fit components. As a dry lubricant in slow moving heavily load sliding surfaces including furnace trolleys.</p> | Lithium | Mineral | # 2/3 | -30/+450 |
| <p>MOLYTACK is available in Aerosol spray can (500 ml)</p> | | | | | | |
| KOPAL KOPAL 500/1000 Copper Based High Temperature Antiseize Pastes | <p>Reduces friction and thereby reduces wear in high pressure sliding surfaces. Prevents seizures at high temperatures. Eases dismantling and assembling during installation and maintenance. Saves threaded parts from galling, distortion and breaking. Guards against rust, normal corrosion and fretting corrosion.</p> | <p>For slow moving and high load applications. For high temperature and corrosive atmospheres. For gears, racks, pinions, spline shafts, plain bearings, pivot joints, bushings, studs, bolts, nuts & other threaded parts. As a live-ring lubricant in cement plants.</p> | Lithium/ Inorganic | Mineral | # 1/2 | -20/+1100 |
| <p>KOPALUBE is available in Aerosol spray can (500 ml)</p> | | | | | | |
| WAP 100 White Assembly Antiseize Paste | <p>Helps prevent staining during assembly. Excellent lubrication properties. Finds use as antiseize and anti stick agent. Prevents water washout. Guards against rust & corrosion.</p> | <p>For machinery used in textile, plastics, food and beverages, instrumentation, optics, electronics, pharmaceutical and related industries where deep colored lubricants are not recommended.</p> | Lithium | Mineral | # 2/3 | -20/+200 |

| PRODUCTS | BENEFITS | APPLICATIONS | BASE | BASE OIL | NLGI GRADE | OPERATING TEMP. RANGE °C |
|--|--|--|---------|----------|------------|--------------------------|
| NTC Nickle Based High Temperature Antiseize Paste | Nickle as solid lubricant provides lubricating action at high temperature. Prevents rust and corrosion. Well suited for humid conditions. Prevents threads from galling and seizing. | For high temperature areas in fertilizers, petrochemicals, chemical plants. As antiseize for fasteners, studs, nuts, bolts, lead screws and other threaded connections installed in very high temperature areas. | Lithium | Mineral | # 2 | -30/+1400 |



To choose the MOLYGRAPH® Product adapted to your requirements, do not hesitate to consult us

Anand Engineers Pvt. Ltd.
 66 M.I.D.C., Road No.13, Andheri (E),
 Mumbai - 400 093. INDIA.
Tel No: +91-22-28219292 \ 98 \ 99
Fax No: +91-22-28379337

Email: sales@molygraph.com
Web: www.molygraph.com